



High quality basic nitrile glove. Good grip. Comfortable and flexible. 13 gauge.

## KEY FEATURES

- Waterproof and oil proof (coating area)
- Good grip in light wet and dry working condition
- OEKO-TEX Standard 100 certified
- Seamless knit for ergonomic fit
- Comfortable and flexible




## PRODUCT DETAILS

Liner	Polyester
Gauge	13
Coating	Nitrile
Finishing	Flat
Colour	Blue / Black
Size	6,7,8,9,10,11,12
Packing	12 pairs/pack, 120 pairs/carton
Tariff number	61161020

## RECOMMENDED APPLICATIONS

**General purpose works under dry working or little wet or little oily conditions.**

Such as general handling, assembly or disassembly works, inspection, logistics, sorting, warehousing, machine operating, adjusting systems, screwing and etc.



## CERTIFICATION


 EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	<b>4</b>
Blade cut - coupe test (Index) (min.0 to max. 5):	<b>1</b>
Tear (min.0 to max. 4):	<b>2</b>
Puncture (min.0 to max. 4):	<b>1</b>
Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to max. F, X - not tested):	<b>X</b>
Impact protection (P if pass, F if failed):	<b>-</b>

EN388:2016



2121X

EN420:2003+A1:2009 Dexterity (min.0 to max.5):  
**level 5.**

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 2103 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals, moving machines or electrical risk.  
Please ensure the products are strictly used within their protection levels.

