



Second Skin Feeling. Innovative new generation glove to redefine flexibility, softness and comfort.

KEY FEATURES

- Extremely light glove with perfect dexterity, flexibility and minimum hand fatigue.
- Much more flexible, soft and comfortable than most of the popular 15 gauge grey nitrile gloves.
- Super soft, comfortable and perfect fitting.
- Improved nitrile coating for extra softness and more durable.
- Super grip in oily and dry working condition.
- OEKO-TEX standard 100 certified for skin friendly.



PRODUCT DETAILS

Liner	Nylon
Gauge	18
Coating	Nitrile
Finishing	Sandy
Colour	Red / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or precision works in dry or light oily conditions.

Such as fine assembly and disassembly, logistics works, equipment maintenance, inspection, sorting, handling small parts, general handling, adjusting systems...



CERTIFICATION

CE EN21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	1
Tear (min.0 to max. 4):	2
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



EN21420:2020 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-008 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

