



New Design – Cut level D, Touch screen function, flexible and comfortable. 13 gauge, PU.

KEY FEATURES

- New design - level D cut protection glove with great abrasion resistance.
- Thanks to the advanced yarns wrapping and knitting technology, it is still soft, flexible and comfortable on a level D cut glove.
- 10-finger touch screen functionality enables you to use all touch screen device on the jobs.
- Ergonomic and good fitting.



PRODUCT DETAILS

Liner	Special yarns
Gauge	13
Coating	Polyurethane
Finishing	
Colour	Grey / Grey
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard in dry conditions.

Such as handling parts with sharp or rough edge materials, automotive industry works, metal sheet handling, assembly, packaging, adjusting systems...



CERTIFICATION

CE EN21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	X
Tear (min.0 to max. 4):	4
Puncture (min.0 to max. 4):	3
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	D
Impact protection (P if pass, F if failed):	-

EN388:2016



EN21420:2020 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-352 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

