



Premium quality, super flexibility, softness and comfort. 13 gauge, special liner, cut level B, XTech PU.

KEY FEATURES

- A premium quality cut level B glove with super flexibility, extra softness, comfort and a cool feeling when wearing in hand.
- Special Xcellent XTech PU formulation contributes to better grip performance, extra softness and comfort.
- Ergonomic, good fitting and great dexterity makes it ideal for general purpose and some precision works.



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	13
Coating	Polyurethane
Finishing	Special XTech
Colour	White / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

RECOMMENDED APPLICATIONS

General purpose, or works with low cut hazard in dry conditions.

Such as handling parts with sharp or rough edges, assembly, inspection, packaging, general handling...



CERTIFICATION

CE EN21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **3**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **B**
Impact protection (P if pass, F if failed): **-**

EN388:2016



EN21420:2020 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-330W can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

