



Specialist eco-friendly glove made using recycled plastic bottles. Very light. 18 gauge, sandy nitrile coating.

KEY FEATURES

- Eco-friendly, to protect our planet and workers. 1 pair equates about 1.6 bottle of 500ml reclaimed and recycled, taken out of landfill and 28 gram CO2 reduced vs using virgin polyester material.
- Very light glove with perfect dexterity, flexibility and less hand fatigue, ideal for general purpose works and precision works.
- Sandy nitrile coating offers great grip performance in dry and oily conditions.



PRODUCT DETAILS

Liner	Recycled Polyester
Gauge	18
Coating	Nitrile
Finishing	Sandy
Colour	Green / Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or precision works in dry conditions.

Such as fine assembly and disassembly, inspection, sorting, handling small parts, general handling, adjusting systems...



CERTIFICATION

CE EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	1
Tear (min.0 to max. 4):	2
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



EN ISO 21420:2020 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-008 EF can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

