



Super thin and comfortable, 18 gauge cut protection level C sleeve. 36cm length.

## KEY FEATURES

- Thanks to 18 gauge knitting technology and quality yams, the sleeve is ultra thin and comfortable.
- Cut protection level C.
- Very stretchable to fit strong and slim arms.
- Extra band design can hold the sleeve in position in the bottom and also more comfortable (compare to a thumb hole design) when wear a glove.



## PRODUCT DETAILS

Liner	UHMWPE, glass fiber, others
Gauge	18
Coating	N.A.
Length	36cm + 7cm band
Colour	Blue
Size	S, XL
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61143000

## RECOMMENDED APPLICATIONS

**General purpose, or works with medium cut hazards.**

Such as handling sharp edge parts, handling electronics parts, handling metal sheets or panels, cutting and etc.



## CERTIFICATION

**CE** EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	<b>2</b>
Blade cut - coupe test (Index) (min.0 to max. 5):	<b>X</b>
Tear (min.0 to max. 4):	<b>4</b>
Puncture (min.0 to max. 4):	<b>X</b>
Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to max. F, X - not tested):	<b>C</b>
Impact protection (P if pass, F if failed):	-

EN388:2016



2X4XC

EN ISO 21420:2020 Dexterity (min.0 to max.5):  
**level 5.**

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 30-910 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals, moving machines or electrical risk.  
Please ensure the products are strictly used within their protection levels.  
Never wear gloves when operating machinery with accessible rotating or other moving parts.

