



ECO Friendly PREMICUT™ Technology 18-gauge cut F sandy nitrile coated glove made with reclaimed and recycled materials. Enhanced dexterity, flexibility, comfort and tactile sensitivity.

KEY FEATURES

- **18-gauge construction** for enhanced dexterity, flexibility, and tactile sensitivity.
- **PREMICUT™ Technology** provides a thinner, smoother, and more comfortable fit without compromising protection performance.
- **Eco-conscious construction** uses reclaimed and recycled material equivalent to approximately one 500 ml plastic bottle per pair.
- **Reduces CO₂ emissions by approximately 18 g per pair** compared with virgin polyester material.
- **Sandy nitrile coating** delivers excellent grip, oil resistance, and durability.
- **Reinforced thumb crotch** enhances durability in a high-wear area, extends glove life, and provides additional protection.



PRODUCT DETAILS

Liner	PremiCut, Recycled Polyester
Gauge	18
Coating	Nitrile
Finishing	Sandy
Colour	Green / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or precision works with high cut hazard in dry or light oily conditions.

Such as precision works, assembly, handling parts with sharp or rough edges, maintenance, general handling, inspection, packaging, sorting...



CERTIFICATION

CE EN ISO 21420:2020

Category II

EN388:2016 Mechanical protection:
levels obtained in laboratory tests

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **2**
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested): **F**
Impact protection (P if pass, F if failed): **-**

EN388:2016



EN ISO 21420:2020 Dexterity (min.0 to max.5):
level 5.

EN407:2020 Heat protection:
levels obtained in laboratory tests

A - Limited flame spread: X of 4
B - Contact heat: 1 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small splashes of molten metal: X of 4
F - Large quantities of molten metal: X of 4

EN407:2020



X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-991 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

