



Engineered with PREMICUT™ Technology advanced 18-gauge cut D uncoated food contact approved glove. This glove provides a smooth, comfortable, close-fitting feel with excellent dexterity and tactile sensitivity.

KEY FEATURES

- **18-gauge construction** for enhanced dexterity, flexibility, and tactile sensitivity.
- **PREMICUT™ Technology** provides a thinner, smoother, and more comfortable fit without compromising protection performance.
- **Food contact approved.** Materials comply with both FDA regulations and EU regulations for food contact.
- **Ultra-thin, close-fitting design** allows comfortable use as a liner or over disposable nitrile or latex gloves.
- **Lightweight construction** helps minimize hand fatigue and support productivity during extended wear.
- **A cool feel** of the material and breathable for all day comfort.
- **Touchscreen compatible** for convenient operation of touchscreen devices.



PRODUCT DETAILS

Liner	PremiCut
Gauge	18
Coating	N.A.
Finishing	N.A.
Colour	Light Blue
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61169300

RECOMMENDED APPLICATIONS

General purpose or precision works with high cut hazard in dry conditions.

Such as precision works, inspection, assembly, printing, sorting, packaging, handling parts with sharp or rough edges, maintenance, general handling...



CERTIFICATION




Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):
Blade cut - coupe test (Index) (min.0 to max. 5):
Tear (min.0 to max. 4):
Puncture (min.0 to max. 4):
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested):
Impact protection (P if pass, F if failed):

EN388:2016



2
X
4
X
D
-

EN ISO 21420:2020 Dexterity (min.0 to max.5):
level 5.

**EN1186 Food Contact Approval Test
results obtained in laboratory tests**

Simulant (s) Used	Test Condition	Result(s) [mg/dm ²]			Maximum Permissible Limit [mg/dm ²]
		1 st migration	2 nd migration	3 rd migration	
3% Acetic acid	70°C for 2 hours	21.4	4.40	<3.0	10
95% Ethanol	60°C for 2 hours	30.8	<3.0	<3.0	10
Iso-octane	40°C for 0.5 hour	15.9	<3.0	<3.0	10
Stability: Comply					

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-903 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

