



A new-generation 18 gauge cut D glove engineered to deliver the lightweight feel and dexterity normally associated with finer-gauge gloves. With a construction approaching the feel of a 21-gauge glove, it provides an excellent balance of cut protection, comfort and precision handling.

KEY FEATURES

- **EN 388 Cut Level D** protection.
- **New-generation 18 gauge** knitted construction, feeling like a 21 gauge but much cheaper.
- Fine-gauge feel with excellent **second-skin comfort**.
- **Outstanding dexterity, flexibility and fit.**
- **Micro-foam nitrile coating** for enhanced grip.
- Good resistance to oil and abrasion.
- Touchscreen compatible.



PRODUCT DETAILS

Liner	UHMWPE, Steel Fiber and Others
Gauge	18
Coating	Nitrile
Finishing	Micro-foam
Colour	Blue / Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or precision works with high cut hazard in dry or light oily conditions.

Such as precision works, assembly, handling parts with sharp or rough edges, maintenance, general handling, inspection, packaging, sorting...



CERTIFICATION

CE EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **2**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **D**
Impact protection (P if pass, F if failed): **-**

EN388:2016



EN ISO 21420:2020 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-981 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

