Xcellent® X-015

Technical Data Sheet





CE CAT. II

EN388 4X43CP

EN407 X1XXXX

15 Gauge

C

Impact, cut, vibration and contact heat protection glove, 15 gauge cut level C. Softer and more comfortable.

KEY FEATURES

- **Good quality TPR pads** offer additional softness and great flexibility.
- **Thanks to the thicker and specially designed TPR pads**, the glove offers better impact protection.
- **New crotch reinforcement** provides a better fit and greater comfort than fabric reinforcement.
- **Extra sponge pad in the palm** offers good vibration protection.
- **Softer and more comfortable than most similar 13-gauge products** on the market.
- **The Velcro design** makes the glove easy to put on and keeps it securely in position while wearing.

PRODUCT DETAILS

Liner	UHMWPE Mixed with Other Yarns
Gauge	15
Coating	Nitrile
Finishing	Sandy
Colour	Hi-vis Yellow / Black
Size	8,9,10,11,12
Packing	6 pairs/pack, 72 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

Works with impact hazard or cut hazard or vibration hazard or contact heat hazard or in challenging light conditions in dry or little oil or little wet conditions.

Typical industry: oil & gas industry, construction industry, automotive industry...

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

CERTIFICATION

CE EN420:2003 + A1:2009

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

EN388:2016



4X43CP

Abrasion (min.0 to max. 4):	**4**
Blade cut - coupe test (Index) (min.0 to max. 5):	**X**
Tear (min.0 to max. 4):	**4**
Puncture (min.0 to max. 4):	**3**
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	**C**
Resistance to impact according to EN 13594:2015 (P if pass, F if failed) :	**P**

EN420:2003+A1:2009 Dexterity (min.0 to max.5): **level 5.**

EN407:2004 Heat protection: levels obtained in laboratory tests

EN407:2004



X1XXXX

A - Burning behaviour:	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small drops of molten metal:	X of 4
F - Large quantity of molten metal:	X of 4

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent X-015 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don’t use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu