Xcellent® 12-350

Technical Data Sheet



Engineered with PREMICUT™ and XTech™ PU coating 13 guage cut D polyurethane coated glove - 20% thinner than other 13 gauge gloves. A smoother, softer, and more comfortable feel.

KEY FEATURES

- Best seller and outstanding 13 gauge cut level D PU glove.
- **PREMICUT™ Technology** makes the glove **more than 20% thinner** than many traditional gloves of comparable 13-guage construction, providing a smoother, softer, and more comfortable feel.
- **Xcellent XTech™ PU coating** delivers good grip with enhanced durability and comfort.
- **Ergonomic design** conforms to the hand for improved fit and freedom of movement.
- **High tactile sensitivity and dexterity** for precise handling and control.

.

CE CAT. II | EN388 4X43D | ANSI A4 CUT | 13 Gauge | D | PremiCut

PRODUCT DETAILS

Liner	PremiCut
Gauge	13
Coating	Polyurethane
Finishing	XTech
Colour	Grey / Grey
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

RECOMMENDED APPLICATIONS

General purpose, or works with high cut hazard in dry conditions.

Such as handling sharp or rough edge materials, metal sheet, assembly, construction, repair, packaging, automotive industry...

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

CERTIFICATION

CE EN ISO 21420:2020

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):	**4**
Blade cut - coupe test (Index) (min.0 to max. 5):	**X**
Tear (min.0 to max. 4):	**4**
Puncture (min.0 to max. 4):	**3**
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	**D**
Impact protection (P if pass, F if failed):	-

EN388:2016



4X43D

EN ISO 21420:2020 Dexterity (min.0 to max.5): **level 5.**

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-350 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don’t use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu