Xcellent® X-017

Technical Data Sheet

Impact, cut and contact heat protection glove, 13 gauge cut level F, more durable double nitrile coating.

KEY FEATURES

- **Thicker and well-designed TPR pads** provide great impact protection, while the high-quality TPR pads are softer, more flexible, and comfortable.
- **Double nitrile coating** offers great durability and puncture resistance, as well as water and oil repellency. The sandy finish provides excellent grip performance.
- **Reinforcement in the thumb crotch** greatly extends glove life and increases abrasion resistance in the weakest area.
- **The hook and loop design** makes the glove easy to put on and take off and keeps it securely in position while wearing.

CE CAT. II | EN388 4X43FP | ANSI A6 CUT | 13 Gauge | F

PRODUCT DETAILS

Liner	UHMWPE, Steel Fiber, Others
Gauge	13
Coating	Nitrile
Finishing	Sandy
Colour	Blue / Black
Size	7,8,9,10,11
Packing	6 pairs/pack, 72 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

Works with impact hazard or cut hazard or vibration hazard or contact heat hazard or in challenging light conditions in dry or little oil or little wet conditions.

Typical industry: oil & gas industry, construction industry, automotive industry...

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

CERTIFICATION

CE EN ISO 21420:2020

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):	**4**
Blade cut - coupe test (Index) (min.0 to max. 5):	**X**
Tear (min.0 to max. 4):	**4**
Puncture (min.0 to max. 4):	**3**
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	**F**
Impact protection (P if pass, F if failed):	**P**

EN388:2016

4X43FP

EN ISO S21420:2020 Dexterity (min.0 to max.5): **level 5.**

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent X-017 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don’t use in case of chemicals or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu