Xcellent® 3006

Technical Data Sheet



CE CAT. II | EN388 4131A | EN407 X1XXXX | 15 Gauge

Lightweight 15 gauge micro foam nitrile coated with dotted palm and heat rated glove offers extended wear and breathability.

KEY FEATURES

- **15-gauge construction** provides a lightweight, flexible feel with excellent dexterity.
- **Micro-foam nitrile coating with additional nitrile dots** enhances grip, abrasion resistance, and durability.
- **High-visibility orange color** improves glove visibility in low-light and outdoor work environments.
- **Soft, flexible construction** provides a comfortable, close-fitting feel for extended wear.
- **Contact heat protection up to 100°C.**
- **Touchscreen compatible** for convenient operation of touchscreen devices.

PRODUCT DETAILS

Liner	Polyester, Spandex
Gauge	15
Coating	Nitrile
Finishing	Micro-Foam, Nitrile Dots
Colour	Orange / Black & Orange
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose work under dry, little wet/little oily working conditions.

Such as assembly and disassembly works, general handling, logistics, maintenance, inspection, sorting, machine operating, screwing, warehouse works...

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

CERTIFICATION

CE EN420:2003 + A1:2009

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

EN388:2016



4131A

Abrasion (min.0 to max. 4):	**4**
Blade cut - coupe test (Index) (min.0 to max. 5):	**1**
Tear (min.0 to max. 4):	**3**
Puncture (min.0 to max. 4):	**1**
Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to max. F, X - not tested):	A
Impact protection (P if pass, F if failed):	-

EN420:2003+A1:2009 Dexterity (min.0 to max.5): **level 5.**

EN407:2020 Heat protection: levels obtained in laboratory tests

EN407:2020



X1XXXX

A - Limited flame spread	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small splashes of molten metal:	X of 4
F - Large quantities of molten metal:	X of 4

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3006 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don’t use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu