Xcellent® 30-745Y

Technical Data Sheet



High visibility top level F cut protection sleeve with an adjustable design for a secure, comfortable fit. Advanced yarn wrapping and knitting technology provides reliable cut protection while maintaining softness and flexibility.

KEY FEATURES

- **Top cut protection at level F.**
- **13-gauge construction** provides an excellent balance of cut protection, flexibility, and comfort.
- **Adjustable upper-arm hook-and-loop closure** provides a secure fit for different arm sizes and helps keep the sleeve in position.
- **Bottom thumb design** helps prevent the sleeve from shifting during use while enhancing comfort.
- **Advanced yarn wrapping and knitting technology** provides reliable cut protection with a soft, comfortable feel.
- **Washable** for extended service life and reduced replacement costs.
- **High visibility color** offers more safety when working in dark or outdoor conditions.

CE CAT. II

EN388 3X4XF

ANSI A6 CUT

13 Gauge

F

PRODUCT DETAILS

Liner	UHMWPE, Steel Fiber, Others
Gauge	13
Coating	N.A.
Finishing	N.A.
Colour	Hi-vis Yellow
Length	45 cm
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61143000

RECOMMENDED APPLICATIONS

General purpose, or works with high cut hazards.

Such as handling sharp edge parts, handling electronics parts, handling metal sheets or panels, cutting and etc.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

CERTIFICATION

CE EN ISO 21420:2020

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

EN388:2016



3X4XF

Abrasion (min.0 to max. 4):	**3**
Blade cut - coupe test (Index) (min.0 to max. 5):	**X**
Tear (min.0 to max. 4):	**4**
Puncture (min.0 to max. 4):	**X**
Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to max. F, X - not tested):	**F**
Impact protection (P if pass, F if failed):	-

EN ISO 21420:2020 Dexterity (min.0 to max.5): **level 5.**

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 30-745Y can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don’t use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu