

## PREMICUT™ Ultra-Thin 18-Gauge Cut Level F Sleeve with thumbhole – Hi-Vis Green.

### KEY FEATURES

- **PremiCut™ engineered yarn technology** provides the ideal balance of lightweight comfort, flexibility, and cut protection level F for demanding work environments.
- **Ultra-thin, breathable construction** delivers a barely-there feel while maintaining reliable protection against cut hazards.
- **Comfort-fit elastic bicep** keeps the sleeve securely in position throughout the workday without pinching or slipping.
- **Built-in thumb slot helps** secure the sleeve in position, while the thin palm knit minimizes bulk under gloves.
- **Bright hi-vis green color** enhances worker visibility and supports PPE compliance in busy industrial settings.
- **Machine washable** for repeated use and long-lasting performance.
- **Offered in 46cm and 56cm lengths** to accommodate different coverage needs.

CE CAT. II | EN388 2X4XF | ANSI A6 CUT | 18 Gauge | F | PremiCut

### PRODUCT DETAILS

| | |
|---|---|
| Liner | PremiCut |
| Gauge | 18 |
| Coating | N.A. |
| Finishing | N.A. |
| Colour | Hi-Vis Green |
| Length | 46cm and 56cm |
| Packing | 12 pairs/pack, 144 pairs/carton |
| Tariff number | 61143000 |

### RECOMMENDED APPLICATIONS

**General purpose, or works with high cut hazards.**

Such as handling sharp edge parts, handling electronics parts, handling metal sheets or panels, cutting and etc.



Xcellent Safety GmbH
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
info@xcellent-safety.eu www.xcellent-safety.eu

## CERTIFICATION

CE EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection: levels obtained in laboratory tests**

| | |
|---|---|
| Abrasion (min.0 to max. 4): | **2** |
| Blade cut - coupe test (Index) (min.0 to max. 5): | **X** |
| Tear (min.0 to max. 4): | **4** |
| Puncture (min.0 to max. 4): | **X** |
| Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to max. F, X - not tested): | **F** |
| Impact protection (P if pass, F if failed): | - |

EN388:2016



2X4XF

EN ISO 21420:2020 Dexterity (min.0 to max.5): **level 5.**

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 30-920 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don’t use in case of chemicals, moving machines or electrical risk. Please ensure the products are strictly used within their protection levels. Never wear gloves when operating machinery with accessible rotating or other moving parts.
Never wear gloves when operating machinery with accessible rotating or other moving parts.



**Xcellent Safety GmbH**
Tel. +49 0211 5407 0207
Lindenstraße 48-50, 40233 Duesseldorf, Germany
**info@xcellent-safety.eu www.xcellent-safety.eu**